



CERTIFICATE OF CONSTANCY OF PERFORMANCE

0766-CPR-632/2

In compliance with Regulation (EU) No 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Melamine faced boards with an improvement to reaction to fire for interior non-structural uses acc. EN 14322

Product name:

Particleboards P2 - EGGER Eurodekor Flammex E1P2 and EGGER Eurodekor Flammex E1E05 P2
thickness range: 8-50 mm according to annex 1

with reaction to fire classification B-s1,d0 and

Particleboard P2 - EGGER Eurodekor Flammex E1P2 and EGGER Eurodekor Flammex E1E05 P2
thickness range: 38-50 mm according to annex 1

with reaction to fire classification B_{fl}-s1

placed on the market under the name / trademark of

SAIB S.p.A.
Via Caorsana, 5/A,
29012 Fossadello PC,
Italy

and produced in the manufacturing plant

SAIB S.p.A.
Via Caorsana, 5/A,
29012 Fossadello PC,
Italy

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13986:2004+A1:2015

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 13. September 2024 and will remain valid as long as neither the harmonised standard EN 13986:2004+A1:2015, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The validation of this certificate will be confirmed by a half-yearly surveillance.

Dresden, 13. September 2024

Date



Dr.-Ing. Rico Emmler
Notified Certification Body

Annex 1

Product types/Receipt no./Product names	Thickness range [mm]	Reaction to fire classification	Technical class of substrate
EN 13986 / EN 312 P2 (fire retardant melamine faced chipboard)			
E1E05 P2 > Recipe 181/191: E1E05P2 CE EAC	8-50 mm 38-50 mm	B-s1,d0 Bfi-s1	P2 P2
E1 P2 > Recipe 1/107/108: E1 P2 CE EAC	8-50 mm 38-50 mm	B-s1,d0 Bfi-s1	P2 P2

This classification is valid for the following end use:

For wall and ceiling cladding

- The construction product may only be used on substrates corresponding to Euroclasses A1 or A2-s1, d0, with a minimum thickness of 9 mm and a minimum bulk density of 653 kg/m³, with the exception of gypsum boards.
- The distance to the before mentioned substrates must be 40 mm and must not be rear-ventilated.
- According to the definition NB-CPR/SH02/19/832r2, installation is also possible directly on the above-mentioned substrates without a gap.
- The installation may only be carried out mechanically using metal fasteners on metal substructures.
- Horizontal and vertical joints with butt-jointed panels.
- Can be used indoors as wall and ceiling cladding.

For floor coverings:

- Can be used as a floor covering (floor conditions: horizontally laid, in interior areas without backlay, with infinite air gap)

ENTWICKLUNGS- UND
PRÜFANOR HOLZ
TECHNOLOGIE GmbH 
Zellescher Weg 24 · 01217 Dresden